

IN THE CLAIMS

The currently pending claims are as follows:

1. (Previously Presented) A multi-channel audio signal processing device comprising:

signal supply means for supplying coded audio signals through several input channels, and for each input channel, through
5 separate sub-channels covering distinct frequency sub-band domains; and

synthesis or reconstruction filters (SFB) for decoding and synthesizing audio signals over the total frequency domain covered by the sub-band domains,

10 characterized in that said multi-channel audio signal processing device further comprises:

sub-band combination circuits, each sub-band combination circuit being supplied with audio signals through respective input channels which lie in one and the same sub-band frequency domain,
15 while the output signals of a sub-band combination circuit covering an associated frequency sub-domain are supplied to one of said synthesis filters for each output channel of said multi-channel audio signal processing device.

2. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 1, characterized in that the

S:\GO\PT07GOC0.GOR

2

multi-channel audio signal processing device further comprises filter means coupled to inputs of the respective synthesis filters.

3. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 1, characterized in that said multi-channel audio signal processing device further comprises filter means coupled between the relevant sub-band combination
5 circuits and the respective synthesis filter.

4. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 1, characterized in that said multi-channel audio signal processing means further comprises filter means coupled between the input sub-channels and inputs of
5 the sub-band combination circuits.

5. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 4, characterized in that the filter means comprise elements for introducing a scale factor.

6. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 2, characterized in that the filter means comprise filters for obtaining a desired virtual spatial widening from which the audio signals can be heard through
5 separate reproduction channels.

S:\GO\PT07GOC0.GOR

3

7. (Previously Presented) The multi-channel audio signal processing device as claimed in claim 2, characterized in that the filter means comprise equalization filters or tone control filters of an alternative kind.

8. (Previously Presented) A method for processing an audio signal comprising the steps:

receiving coded audio signals in different frequency sub-band areas;

5 combining the coded audio signals in different frequency sub-bands to form combined signals; and

synthesis filtering and decoding the combined signals.